



Olten

High Bay with Prismatic Refractor

Olten is a comprehensive range of stylish High Bay luminaire designed to accommodate most commercial interiors including retail stores, car show rooms, reception areas and university buildings.

Available in two sizes, 420mm or 570mm, the Olten can be surface mounted or suspended, and consists of compact fluorescent and HQI discharge versions. It is also supplied with integral mains gear and a high-performance polycarbonate refractor as standard (additional light diffusion can be provided with the optional lens cover).

Optional integral emergency versions are available with the 42W or 57W lamps enabling the Olten to be considered for most prestigious installations where separate emergency luminaires are not acceptable.



Olten 420mm



Olten 570mm

Mains Luminaires

Cat No.	Lamp	Lumens	Kg
OLT242A	2 x 42W TC-T	-	4.00
OLT57A	57W TC-T	-	4.00
OLT70A	70W HQ-I	-	4.50
OLT85A	85W PL-H	-	4.50
OLT150A	150W HQ-I	-	8.00
OLT120B	120W PL-H	-	8.00
OLT250B	250W HQ-I	-	9.20
OLT400B	400W HQ-I	-	10.80

Emergency Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
OLT242A/M3	M3 2 x 42W TC-T (one lamp in emergency)	580	5.80
OLT57A/M3	M3 57W TC-T	560	5.90

Slave Luminaires

Cat No.	Mode/Lamp	Lumens*	Kg
OLT242A/PVR/#	Slave 2 x 42W TCT-T (one lamp in emergency)	770	4.00
OLT57A/PVR/#	Slave 57W TC-T	860	4.00

Options Suffix:

- /LCA Lens cover A size
- /LCB Lens cover B size
- /SK Suspension kit

Specify 24, 50, 110 or 230 Volts AC/DC System Voltage

* Not suitable for use with lamps with integral ignitors

Dimensions: Mains A size: 410 Ø x 470mm

Mains B size: 570 Ø x 570mm

Emergency A size: 410 Ø x 550mm

IP20  